

# Elite Roman Blind Order Form

Account Number	Date
Account Name	
Your order reference	
Delivery Address	
(If left blank, we will assume that delivery is to your standard delivery address)	

### IMPORTANT INFORMATION

#### INSTALLATION HEIGHT (FIXED TENSION DEVICE):

We are required by law to ask for the height of installation, so that we can ensure the bottom of chain loop we supply is a minimum of 150cm from the floor. If you do not know your installation height, you are able to specify "unknown". If specifying "unknown", we will supply a chain in the colour of your choice that will give a 100cm drop - We recommend discussing this with your fitter prior to placing your order, as they may be required by law to shorten the chain in order to conform to BS EN 13120 child safety legislation.

When creating Roman Blinds with panels over 20cm, Rear Cord Breakaway devices are required on the last and penultimate point.

#### REAR CORD BREAKAWAY DEVICES:

If the rods on your roman blind will be spaced any greater than 20cm apart, you are required by law to fit a break away device to the rear cords in order to conform to BS EN 13120 child safety legislation. Our break away devices can be supplied as an optional extra for these circumstances. For pricing information, please refer to the price guide.

**DID YOU KNOW?** You can get a quote and place Elite Made to Measure orders online via our webshop: [www.halliswebshop.com](http://www.halliswebshop.com) : will ask you all of the relevant questions, making your ordering process easy, ensuring you order a fully compliant blind every time.

## Elite Standard Specification

(Optional upgrades available at an additional cost, please refer to Roman Blind price list)

Detail	Standard Specification	Additional options
Length	Chain	Motorised, Crank Operated
Gear Ratio	Up to 250cm = 1:1 (6kg max) Over 250cm = 1:4 (10kg max)	1:1 or 1:4 available for all sizes
Chain Colour	White	Chrome, Antique Brass, Bright Brass, Black Nickel, Bronze
Chain Safety Device	0934R: Inside recess fixed tension safety device, clear	0941R: Outside recess fixed tension device, clear or white CS1001: Outside recess chain tension device (metal), antique brass, brushed steel or white CS1100: Chain breakaway device (plastic), white, black, gunmetal 0908R: Chain breakaway connector (1:1 gear ratio only) 1005R/Size: Continuous chain with breakaway (white chain only)
Chain Length	The longest length available within legislation	Any desired length within legislation and within the restrictions of your chosen safety device
Wand Length	N/A	50cm, 75cm, 100cm, 150cm, 250cm
Chain Side	Right	Left
Bracket Type	Universal lever lock	Leverlock (easy open), Spring, Adjustable, Valance, Swivel
Number of Cord Spools	1 spool every 60cm, plus 1	Up to 2 additional spools
Cord Colour	White	Off White, Sand, Black, Grey, Taupe, Vanilla, Dark Grey, Old Rose, Bordeaux, Red, Green, Light Blue, Marine
Rear Cord Safety Device	None	CSTOGGLE/SEW: Sew in adjustable toggle, 1 per cord spool CSTOGGLE/CLIP: Clip on adjustable toggle, 1 per cord spool 0958R: Sew on breakaway device, 2 per cord spool & 0988R Adjustable toggle CS/CLIP: Clip on breakaway device, 2 per cord
Rods & Bottom Bar	None	7 Rods & 1 Bottom Bar cut 2cm narrower than the headrail
Battery Tube Mounting	Headrail - Clip on Brackets underneath headrail	Wall - Clip on brackets fixable to the wall

ALL HEADRAILS								CHAIN OPERATED								MOTORISED		
Qty	Finished Length (cm)	Control Type (Chain / Motorised)	Bracket Type (Item No.)	Rear Cord Colour	Are Rear Cord Devices required? (Item No.)**	Are Rods and Bottom Bars required? (Item No.)*	Location	Are Chain Breakaway Devices required? (Item No.)*	Chain Colour	Gear Housing (1:1/1:4)	Touch & Close End Cap	Control Side (LH/RH)	Installation Height (cm)*	Blind Drop (cm)*	Chain Drop (cm)*	Power Option	Battery Tube Mounting (Headrail/Wall)	Control (Item No.)

\* IN ORDER TO CONFORM TO CHILD SAFETY LEGISLATION:  
Your chain drop must be at least 150cm less than your installation height (or 60cm when choosing a Chain Breakaway Device).

\*\* If the rods on your roman blind will be spaced any greater than 20cm apart, you will require break away devices.