

Professional Chain/Dual Rise Blind Order Form

Account Number

Date

Account Name

Your order reference

Delivery Address

(If left blank, we will assume that delivery is to your standard delivery address)

Standard Specification

(Optional upgrades available at an additional cost, please refer to Roman Blind price list)

Detail	Standard Specification	Additional options
Control Type	Chain	Dual Rise (Chain or Wand)
Gear Ratio	Up to 150cm = 1:1 (3kg max) Over 150cm = 1:4 (6kg max)	
Chain Colour	Dual Rise - 75cm chrome Chain Operated - 100cm Plastic	Plastic: White Metal: Antique Brass, Bright Brass, Bronze, Black Nickel
Chain Safety Device (Chain operated only)	Dual Rise	0934R: Inside recess chain tension device, clear 0941R: Outside recess chain tension device, clear or white CS1001: Outside recess chain tension device (Metal) antique brass, brushed steel or white 12124R/CS: Integrated Chain Breakaway (1:4 gear ratio only) CS1100: Chain breakaway device (Plastic) white, black or gunmetal 0908R: Chain breakaway connector (1:1 gear ratio only) 1005R/Size: Continuous chain with breakaway (white chain only)
Wand Colour	Silver	N/A
Wand Length (Dual Rise only)	N/A	50cm, 60cm or 100cm
Chain Length (Dual Rise only)	The longest length available with legislation	Any desired length within legislation and within the the restrictions of your chosen safety device
Pull Tassel	Metal: Chrome	Metal: White, Brushed Silver, Antique Brass, Black Nickel Plastic: White, Cream, Bronze, Grey, Anthracite, Black
Control Side	Right	Left
Bracket Type	Universal lever lock	Clip on bracket
Number of Cord Spools	1 spool every 60cm, plus 1	Upto 2 additional spools
Rear Cord Breakaway Device	None	CSTOGGLE/SEW: Sew in adjustable toggle, 1 per cord spool CSTOGGLE/CLIP: Clip on adjustable toggle, 1 per cord spool 0958R: Sew in break away device, 2 per cord spool CS/CLIP: Clip on break away device, 2 per cord spool

IMPORTANT INFORMATION

INSTALLATION HEIGHT (FIXED TENSION DEVICE):

We are required by law to ask for the height of installation, so that we can ensure the bottom of chain loop we supply is a minimum of 150cm from the floor. If you do not know your installation height, you are able to specify "unknown". If specifying "unknown", we will supply a chain in the colour of your choice that will give a 100cm drop - We recommend discussing this with your fitter prior to placing your order, as they may be required by law to shorten the chain in order to conform to BS EN 13120 child safety legislation.

When creating Roman Blinds with panels over 20cm, Rear Cord Breakaway devices are required on the last and penultimate point.

REAR CORD BREAKAWAY DEVICES:

If the rods on your roman blind will be spaced any greater than 20cm apart, you are required by law to fit a break away device to the rear cords in order to conform to BS EN 13120 child safety legislation. Our break away devices can be supplied as an optional extra for these circumstances. For pricing information, please refer to the price guide.

Qty	Finished Length (cm)	Control Type (Chain or Dual Rise)	Gear Ratio (1:1 or 1:4)	Control Side (LH/RH)	Chain Colour	Installation Height (cm)	Blind Drop (cm)	Chain Drop (cm)	Chain Pull Colour	Wand Size (Dual Rise only)	Bracket Type	Additional Cord Spools (upto 2 extra)	Are Chain Breakaway / Safety Devices required? (Item No.)	Are Rear Cord Breakaway Devices Required? (Item No.)	No. of Rods & Bottom Bars	Length of Rods & Bottom Bar (cm)	Location